

# Rack Cabinets Catalogue

## Server Rack Cabinet



### Product Description:

- Classic model, disassembled structure, can be flat packing and easy to transport.
- Tempered glass or perforated steel front door with advanced spring lock, Steel rear door with spring lock.
- Removable side panel with latches, easy to install, optional lock.
- Cable entry on the top and bottom, easy to manager cable.
- Adjustable feet and castors are available simultaneously.
- S-shaped mounting profile, free to move forward and back.
- Various optional accessories for common using.

### Product Parameters:

- Comply with ANS/ EIA RS-310- D, IEC297-2, DIN41491, PART1, DIN41491, PART7, ETSI Standard.
- SPCC quality cold rolled steel.
- Mounting profile 2.0mm(others: 1.0-1.2mm)
- Body Color: RAL9004, RAL9005, RAL7035
- Static loading: 800kg-1000kg



Vented Front



Overhead Fan



Shelf



Spring Lock



Thickened Mounting Profile



Removable Side Door

# Rack Cabinets Catalogue

## Server Rack Cabinet

| Item No   | U Capacity | Front Door(X)                              | Rear Door(Y)             | Size |      |      |
|-----------|------------|--------------------------------------------|--------------------------|------|------|------|
|           |            |                                            |                          | W    | D    | H    |
| HER2766XY | 27U        | S = Perforated Steel                       | 1 = 1 Door               | 600  | 600  | 1400 |
| HER2768XY |            | G = Tempered Glass                         | 2 = 2 Door               | 600  | 800  | 1400 |
| HER3266XY | 32U        | S = Perforated Steel<br>G = Tempered Glass | 1 = 1 Door<br>2 = 2 Door | 600  | 600  | 1600 |
| HER3268XY |            |                                            |                          | 600  | 800  | 1600 |
| HER3261XY |            |                                            |                          | 600  | 1000 | 1600 |
| HER3288XY |            |                                            |                          | 800  | 800  | 1600 |
| HER3281XY |            |                                            |                          | 800  | 1000 | 1600 |
| HER3766XY | 37U        | S = Perforated Steel<br>G = Tempered Glass | 1 = 1 Door<br>2 = 2 Door | 600  | 600  | 1800 |
| HER3768XY |            |                                            |                          | 600  | 800  | 1800 |
| HER3761XY |            |                                            |                          | 600  | 1000 | 1800 |
| HER4266XY | 42U        | S = Perforated Steel<br>G = Tempered Glass | 1 = 1 Door<br>2 = 2 Door | 600  | 600  | 2000 |
| HER4268XY |            |                                            |                          | 600  | 800  | 2000 |
| HER4261XY |            |                                            |                          | 600  | 1000 | 2000 |
| HER4288XY |            |                                            |                          | 800  | 800  | 2000 |
| HER4281XY |            |                                            |                          | 800  | 1000 | 2000 |
| HER4766XY | 47U        | S = Perforated Steel<br>G = Tempered Glass | 1 = 1 Door<br>2 = 2 Door | 600  | 600  | 2200 |
| HER4768XY |            |                                            |                          | 600  | 800  | 2200 |
| HER4761XY |            |                                            |                          | 600  | 1000 | 2200 |
| HER4788XY |            |                                            |                          | 800  | 800  | 2200 |
| HER4781XY |            |                                            |                          | 800  | 1000 | 2200 |